Miniature PCB Power Relay

HG4124L

FEATURES

- 20A contact capacity
- 1 Form A, 1 Form B and 1 Form C contact form for choice
- 4 KV dielectric strength between coil and contacts
- Sealed and dust cover version available
- UL, CUR, TUV approved

TYPICAL APPLICATIONS

- Household appliances
- Office machine
- Vending machine
- Air conditioner, refrigerator

CONTACT RATING

Form	1 Form A (1H), 1 Form B (1D), 1 Form C (1Z)
Rated Load	16A, 240VAC/24VDC; 1HP, 240VAC
Max. Switching Current	20A
Max. Switching Voltage	277VAC/30VDC
Max. Switching Power	3840VA/384W

CONTACT DATA

Material		AgCdO
Initial Contact Resistance		50 mΩ max. at 1A, 24VDC
Service Life	Mechanical	10^7 ops.
	Electrical	10^5 ops.

UL/CUR RATING

	1 Form A (1H) 1 Form C (1Z) NO	1 Form B (1D) 1 Form C (1Z) NC
General Use	16A, 240VAC	
Resistive	20A, 277VAC / 24VDC	
Motor	1HP, 240VAC	

COIL DATA

Coil Voltage Code	Nominal Voltage (VDC)	Resistance (Ω) ±10%				Must Operate Voltage max. (VDC)	Must Release Voltage min. (VDC)
		Power Consumption					
		Standard		Sensitive			
005	5	36	0.72W	47	0.55W	3.6	0.5
006	6	50		68		4.3	0.6
009	9	115		160		6.5	0.9
012	12	200		275		8.6	1.2
018	18	460		650		13.0	1.8
024	24	820		1100*		17.3	2.4
048	48	3300*		4170*		34.6	4.8
060	60	5100*		7000*		43.2	6.0

CHARACTERISTICS

Operate Time	15 ms. max.
Release Time	5 ms. max.
Insulation Resistance	1000 MΩ, at 500 VDC, 50%RH
Dielectric Strength	4000 Vrms, 1 min. between coil and contacts 1000 Vrms, 1 min. between open contacts
Shock Resistance	10 g, 11ms. functional; 100g, destructive
Vibration Resistance	DA 1.5mm, 10 - 55 Hz
Ambient Temperature	-40°C to 70°C
Weight	18.5 g, approx.

ORDERING DESIGNATION

Example:	HG4124L /	012 -	1Z	1	H

Model

Coil Voltage Code

Contact Form
1H: 1 Form A; 1D: 1 Form B; 1Z: 1 Form C

Version
1: Sealed; 2: Dust Cover

Coil Sensitivity
Nil: Standard 0.72W; H: Sensitive 0.55W

REFERENCE CURVES



OVERALL DIMENSIONS, MOUNTING HOLES AND WIRING DIAGRAMS (mm)

Overall Dimensions



Mounting Holes (Bottom View)



Wiring Diagrams (Bottom View)



NOTES

1. All parameters, unless otherwise specified, are measured at ambient temperature 23 ºC.
2. Coil resitance with * mark is ±15%.
3. Custom-made services available with operational quantity. Please let us know your special requirements.
4. Specifications subject to change without prior notice.

DB LECTRO INC. 3600 boul. Matte suite I Brossard Qc J4Y-2Z2

TEL:(450)-444-1424 FAX: (450)-444-4714